## VACUUM LIFTERS tilting 180°

Standard Lifting Capacities	Available Power Systems	Load Movement				
up kg 300	✓ COMPRESSED AIR	✓ manual tilt 0°-180°				
	✓ INDEPENDENT ELECTRIC VACU	UM PUMP				

Vacuum lifter with the possibility of tilting a load 180 degrees.

Standard features	Available options			
✓ adjustable handle	customized dimensions of pads and lifting capacities			
✓ reserve of vacuum with filter of aspiration for dust and condense	vacuum gasket seals for particular applications			
$\checkmark$ on-off double sliding valve with safety	hoses for connection (vacuum and pneumatic)			
✓ two non-return valve				
✓ acoustic and visual alarm independently powered				
✓ vacuum gauge with colored scale				
✓ lockable tilting at 0 and 90 degrees				

## Vacuum Lifters

are available lifter with different LIFTING CAPACITY and DIMENSIONS OF PADS

Capacity (kg)	125	250	300		
Number of pad	1	1	1		
Dimension of pad (mm)	745 x 210				
Operating System					
COMPRESSED AIR					
	M1A 125 T	M1A 250 T	M1A 300 T		
WITH INDEPENDENT ELECTRIC VACUUM PUMP ( pump not included )					
	M1E 125 T	M1E 250 T	M1E 300 T		

We reserve the right to make constructive amendments