VACUUM LIFTERS for kitchen tops

Standard Lifting Capacities	Available Power Systems	Load Movement
up kg 550	✓ COMPRESSED AIR	✓ manual tilt 0°-90°
	✓ ELECTRIC AC 110v/220v/400v – DC 12v/24v	✓ pneumatic tilt 0°-90°
	✓ INDEPENDENT ELECTRIC VACUUM PUMP	✓ electric tilt 0°-90°
	✓ BATTERY	✓ fixed frame





Vacuum lifters with grip pads indicated for lifting and handling shaped material with little space available for supporting the suction pads. Particularly suitable for kitchen tops.

Standard features	Available options
✓ length of structure 2000 mm	> customized dimensions of pads and lifting capacities
✓ sliding adjustable pads, individual pad shutoffs	> vacuum gasket seals for particular applications
✓ adjustable handle (on mod. M)	➤ low headroom frame
✓ vacuum gauge with colored scale	➤ economizer of compressed air or electric
✓ on-off double sliding valve with safety	➤ adjustable handle for mod. P / O
✓ two non-return valve	➤ hoist control support on handle
✓ filter of aspiration for dust and condense	➤ hoses for connection (vacuum and pneumatic)
✓ acoustic and visual alarm independently powered	➤ fittings or quick release connections
✓ vacuum tank with stopper for clearing and condensate discharge	e > battery charger (for battery powered models)
✓ lockable tilting at 0 and 90 degrees (on mod. M)	
✓ galvanized structure and varnished vacuum tank	

Vacuum Lifters are available lifter with different LIFTING CAPACITY and DIMENSIONS OF PADS

Capacity (kg)	330	440	550
Number of pads	3	4	5
Dimension of pad (mm)	580 x 180	580 x 180	580 x 180
Operating System / Movement			
COMPRESSED AIR			
Manual	M3A 330	M4A 440	M5A 550
Pneumatic	P3A 330	P4A 440	P5A 550
ELECTRIC AC with on board vacuum pump 110v/220v/400v	/ – different Voltage on reques	t *	
Manual	M3EB 330	M3EB 440	M3EB 550
WITH INDEPENDENT ELECTRIC VACUUM PUMP (pump no	t included) *		
Manual	M3E 330	M3E 440	M3E 550
BATTERY POWERED, complete with ELECTRIC VACUUM PUN	MP 12 o 24 Volt **		
Manual / 12 Volt	M3B12V 330	M4B12V 440	M5B12V 550
Manual / 24 Volt	M3B24V 330	M4B24V 440	M5B24V 550

^{*} On request are available models with pneumatic or electric tilt

We reserve the right to make constructive amendments